

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

1. A liquid crystal display element comprising:
 - a first electrode substrate having a first transparent substrate, a first electrode formed on said first substrate, and a first alignment layer formed on said first substrate so as to cover said first electrode;
 - a second electrode substrate having a second transparent substrate, a second electrode formed on said second substrate, and a second alignment layer formed on said second substrate so as to cover said second electrode; and
 - a light modulating layer of an anti-ferroelectric liquid crystal material which is sandwiched between said first and second electrode substrates covered with first and second alignment layers and which has a thresholdless voltage-transmittance characteristic,wherein said first and second alignment layers are combined with said liquid crystal material so that a shifted angle between the extending direction and an optical axis of a *batonnet* is within ± 1 degree.
2. A liquid crystal display element as set forth in claim 1, wherein the optical axis of a *batonnet* deposited from said first electrode substrate is substantially coincident with the optical axis of a *batonnet* deposited from said second electrode substrate.
3. A liquid crystal display element as set forth in claim 1, wherein said first and second alignment layers have a surface tension of 49 dyn/cm to 53 dyn/cm.
4. A liquid crystal display element as set forth in claim 2, wherein said first and second alignment layers have a surface tension of 49 dyn/cm to 53 dyn/cm.
5. A liquid crystal display element as set forth in claim 1, wherein said first electrode substrate is an array substrate comprising: a plurality of scanning lines and signal lines, which are provided on said first substrate in the form of a matrix;

switching elements, each of which is formed at a corresponding one of the intersections between said scanning lines and said signal lines, one end of each of said switching elements being connected to a corresponding one of said signal lines, each of said switching elements being open and closed in response to a signal of a corresponding one of said scanning lines; pixel electrodes, each of which is connected to the other end of a corresponding one of said switching elements; and said first alignment layer formed on said first substrate so as to cover said pixel electrodes, and

said second electrode substrate is a counter substrate comprising a counter electrode formed on said second substrate, and said second alignment layer formed on said second substrate so as to cover said counter substrate.

6. A liquid crystal display element as set forth in claim 2, wherein said first electrode substrate is an array substrate comprising: a plurality of scanning lines and signal lines, which are provided on said first substrate in the form of a matrix; switching elements, each of which is formed at a corresponding one of the intersections between said scanning lines and said signal lines, one end of each of said switching elements being connected to a corresponding one of said signal lines, each of said switching elements being open and closed in response to a signal of a corresponding one of said scanning lines; pixel electrodes, each of which is connected to the other end of a corresponding one of said switching elements; and said first alignment layer formed on said first substrate so as to cover said pixel electrodes, and

said second electrode substrate is a counter substrate comprising a counter electrode formed on said second substrate, and said second alignment layer formed on said second substrate so as to cover said counter substrate.

7. A liquid crystal display element as set forth in claim 3, wherein said first electrode substrate is an array substrate comprising: a plurality of scanning lines and signal lines, which

are provided on said first substrate in the form of a matrix; switching elements, each of which is formed at a corresponding one of the intersections between said scanning lines and said signal lines, one end of each of said switching elements being connected to a corresponding one of said signal lines, each of said switching elements being open and closed in response to a signal of a corresponding one of said scanning lines; pixel electrodes, each of which is connected to the other end of a corresponding one of said switching elements; and said first alignment layer formed on said first substrate so as to cover said pixel electrodes, and

said second electrode substrate is a counter substrate comprising a counter electrode formed on said second substrate, and said second alignment layer formed on said second substrate so as to cover said counter substrate.